

CS250

Performance worthy of an encore
and functional design for the workplace



Refreshing water for any working environment

With a choice of hot and cold the CS250 is a popular choice for offices and factories where great quality water is required.

Advanced technology

The CS250 features three core technologies:



High performance filtration

Multi-stage filtration removes common water contaminants and chlorine to dramatically improve water taste and odor.



In-tank UV sanitization

In-tank UV technology acts against waterborne micro-organisms and bacteria, dispensing great quality water glass after glass.



BioCote® protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides an effective barrier against microbes like bacteria and mold, which may cause odors or staining.

Simply great, clear water*

Free from fluoride (dependent on filters type and water conditions)

Free from chlorine (dependent on filters type and water conditions)

Free from water-borne tastes and odors

*Filtration results based on the use of RO, GAC, CBC or sediment filters.

Features

In-tank UV technology is highly effective against germs and bacteria. A UV lamp treats the water stored in the reservoir for fast, reliable and easy water purification

Removable drip tray to collect accidental spillage

BioCote® protected dispensing area

Thermal overload protection

Easy connection to the existing water supply

Leak detection for peace of mind

Water options

cold



sparkling

ambient

hot



extra hot

Number of users



10 - 30

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding:

13.6"/345mm (W) x 40.2"/1022mm (H) x 14.4"/367mm (D)

Countertop:

13.6"/345mm (W) x 17.7"/450.5mm (H) x 14.4"/367mm (D)

Dispensing area height

8.5"/215.9mm

Weight

Freestanding: 58lbs (26.3kg)

Tabletop: 42lbs (19.1kg)

Recommended filtration

Sediment, GAC, CBC with lead and cyst removal
(Dependent on local water conditions)

Storage capacity

Hot tank: 1.6 liters

Cold tank (Freestanding): 4 liters

Cold tank (Countertop): 2 liters

Drip tray capacity

0.4 US gal

Compressor

120V/60Hz

Water temperatures settings

Cold: 37-54°F (default 41°F)/2.7-12°C (default 5°C)

Hot: 187°F /86°C



Tested and certified



CE QUALITY & SAFETY
GUARANTEED

ClearSkyH2O.com
469.638.3800