

CS270

Sturdy design and steady performance
for quality water



Reliable performance

Easy operation, robust design and durable materials, make the CS270 the perfect fit even for demanding environments. The gravity fed system makes this machine ideal for areas with low water pressure or situations where incoming water conditions require the use of reverse osmosis.

Advanced technology

The CS270 features three core technologies:



High Performance Filtration

This model can be configured with four stage reverse osmosis filtration or multi stage carbon filtration, depending on water conditions. These filtration processes effectively remove water contaminants and chlorine to improve water taste and odor



In-tank UV sanitization

In-tank UV technology acts against waterborne microorganisms and bacteria, dispensing great quality water glass after glass.



BioCote® protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides an effective barrier against microbes like bacteria and mold, which may cause odors or staining.

Simply great, clear water

Free from chlorine (dependent on filters type and water conditions)

Free from waterborne tastes and odors

Features

Multiple filtration options to fit specific water conditions. A choice of carbon filtration or reverse osmosis, ideal to address poor incoming water conditions

Gravity-fed system, particularly suitable for low pressure installations, also guarantees water supply in case of power outage

The in-tank sanitizing system ensures water is exposed to the UV light to maintain the microbiological purity of the water

Faults indicators for easier servicing

BioCote® protected reservoir and dispensing area (including drip tray body, cold faucet, user interface panel and buttons)

Leak detection for peace of mind

Water options

cold



sparkling

ambient



hot



extra hot

Technical specifications

Types available

Freestanding

Dimensions

15.39"/391mm (W) x 45.70"/1161mm (H) x 14.40"/366mm (D)

Dispensing area height

9.0"/228.6mm

Weight

60lbs/~ 27.21kg

Standard filtration recommended

Reverse osmosis or 1 x Carbon filter

Storage capacity

Ambient reservoir: 11.4 liters

Cold tank: 4 liters

Total capacity: 15.4 liters

Hot tank 1.6 liters

Compressor

110V (60 Hz)

Water temperature settings

Cold: 41 °F/5 °C (factory set point)

Hot: 181 °F/82.77 °C (factory set point)

Number of users

 30 - 50

Tested and certified



CE QUALITY & SAFETY
GUARANTEED

ClearSkyH2O.com
469.638.3800